

## DS-2CD2443G0-I(W) 4 MP EXIR Fixed Cube Network Camera



### Key Features

- 2688 × 1520@30fps
- IR: 10 m
- PIR: 10 m
- H.265+. H.265
- 120dB WDR
- Built-in MicroSD/SDHC/SDXC slot, up to 128G
- PoE
- EXIR
- Wi-Fi (Optional)



[www.hikvision.com](http://www.hikvision.com)

## Specifications


| <b>Camera</b>               |  |
|-----------------------------|--|
| Image Sensor                | 1/3" Progressive Scan CMOS   |
| Min. Illumination           | Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR                                 |
| Shutter Speed               | 1/3 s to 1/100,000 s   |
| Slow Shutter                | Yes  |
| Day & Night                 | IR Cut Filter  |
| Digital Noise Reduction     | 3D DNR   |
| WDR                         | 120dB  |
| 3-Axis Adjustment           | Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°   |
| <b>Lens</b>                 |  |
| Focal length                | 2.8 mm   |
| Aperture                    | F1.6   |
| FOV                         | 2.8 mm: horizontal FOV: 98°, vertical FOV: 55°, diagonal FOV: 114°   |
| Lens Mount                  | M12  |
| <b>IR</b>                   |  |
| IR Range                    | 10 m   |
| Wavelength                  | 850nm  |
| <b>PIR</b>                  |  |
| Angle                       | Horizontal: 90°, Vertical: 80°   |
| PIR Range                   | 10 m   |
| <b>Compression Standard</b> |  |
| Video Compression           | Main stream: H.265/H.264<br>Sub-stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264                     |
| H.264 Type                  | Main Profile/High Profile  |
| H.264+                      | Yes  |
| H.265 Type                  | Main Profile   |
| H.265+                      | Yes  |
| Video Bit Rate              | 32 Kbps to 16 Mbps   |
| Audio Compression           | G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM  |
| Audio Bit Rate              | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)  |
| <b>Smart Feature-set</b>    |  |
| Behavior Analysis           | Line crossing detection, intrusion detection   |
| Face Detection              | Yes  |
| Region of Interest          | Support 1 fixed region for main stream and sub-stream separately   |
| <b>Image</b>                |  |
| Max. Resolution             | 2688 × 1520  |
| Main Stream                 | 50Hz: 25fps (2688 × 1520, 2304 × 1296, 1920 × 1080)<br>60Hz: 30fps (2688 × 1520, 2304 × 1296, 1920 × 1080) |
| Sub-Stream                  | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)<br>60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)             |
| Third Stream                | 50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288)<br>60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)           |

|                               |  |
|-------------------------------|--|
| Image Settings                | Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser                          |
| Image Enhancement             | BLC/3D DNR   |
| Day/Night Switch              | Auto/Schedule  |
| <b>Network</b>                |  |
| Network Storage               | Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR  |
| Alarm Trigger                 | Motion detection, video tampering, network disconnected, IP address conflict, HDD full, HDD error, PIR, illegal login          |
| Protocols                     | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, QoS, IPv6               |
| General Function              | One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter |
| API                           | ONVIF (PROFILE S, PROFILE G), ISAPI  |
| Simultaneous Live View        | Up to 6 channels   |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator and User   |
| Client                        | iVMS-4200, Hik-Connect, iVMS-5200, iVMS-4500   |
| Web Browser                   | IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+   |
| <b>Interface</b>              |  |
| Audio                         | 1 built-in mic, 1 built-in speaker, mono sound   |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port  |
| On-board storage              | Built-in Micro SD/SDHC/SDXC slot, up to 128G   |
| SVC                           | Support H.264 and H.265 encoding   |
| Reset Button                  | Yes  |
| <b>Wi-Fi (-W)</b>             |  |
| Wireless Standards            | IEEE 802.11b/g/n   |
| Frequency Range               | 2.412 GHz to 2.4835 GHz  |
| Channel Bandwidth             | 20M/40M  |
| Protocols                     | 802.11b: DQPSK, DBPSK, CCK<br>802.11g/n: OFDM/64-QAM, 16-QAM, QPSK, BPSK   |
| Security                      | WPA, WPA2  |
| Transfer Rates                | 11b: 11Mbps, 11g: 54Mbps, 11n: up to 150Mbps   |
| Wireless Range                | 50 m   |
| <b>Audio</b>                  |  |
| Environment Noise Filtering   | Yes  |
| Audio Sampling Rate           | 16 kHz   |
| <b>General</b>                |  |
| Operating Conditions          | -10 °C to +40 °C (14 °F to +104 °F), Humidity 95% or less (non-condensing)   |
| Power Supply                  | 12 VDC ± 25%, PoE (802.3af, class 3)   |
| Power Consumption and Current | 12 VDC, 0.5 A, max. 6 W, Φ 5.5 mm coaxial plug power<br>PoE (802.3af, 36V to 57V), 0.2 A to 0.1 A, max. 7W                     |
| Material                      | Plastic  |
| Dimensions                    | 102.8 mm × 65.2 mm × 32.6 mm (4.1" × 2.6" × 1.3")  |
| Weight                        | Camera: Approx. 128 g (0.3 lb.)  |

## Available Models:

DS-2CD2443G0-I (2.8 mm), DS-2CD2443G0-IW (2.8 mm)

## Dimensions



Distributed by

**ООО Компания "Строимир"**  
г. Киев, ул. Борщаговская 154А, оф. 435  
+38 (044) 331-15-43 info@smartel.ua  
https://smartel.ua

## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
potand@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

05050520180326